

3A, 45V Low Forward Voltage Schottky Rectifier

FEATURES

- Ideal for automated placement
- High junction temperature to 175°C
- Low power loss, high efficiency
- Low forward voltage drop
- Moisture sensitivity: level 1, per J-STD-020
- High temperature soldering guaranteed: 260°C/10 seconds
- RoHS compliant
- Halogen-free according to IEC 61249-2-21 definition

SMA

**RoHS
COMPLIANT**
**HALOGEN
FREE**

MECHANICAL DATA

- Case: SMA
- Case material: molding compound meets UL 94V-0 flammability rating
- Polarity: color band denotes cathode end

TYPICAL APPLICATION

General purpose use in rectification for SMPS, lighting, adapter, charger, home appliance, office equipment and telecommunication.

MAXIMUM RATINGS

$T_A=25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Value	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	45	V
Average Forward Rectified Current	$I_{F(AV)}$	3	A
Peak Forward Surge Current (8.3 ms single half sine-wave superimposed on rated load)	I_{FSM}	80	A
Operating Junction Temperature Range	T_J	-55 to +175	°C
Storage Temperature Range	T_{STG}	-55 to +175	°C

ELECTRICAL CHARACTERISTICS

$T_A=25^\circ\text{C}$ unless otherwise noted

Parameter	Test Conditions	Symbol	Value		Unit
			Typ.	Max.	
Forward Voltage @ $I_F=3\text{A}$	$T_A=25^\circ\text{C}$	V_F	0.43	0.46	V
	$T_A=125^\circ\text{C}$		0.37	0.4	
Reverse Current @ V_{RRM}	$T_A=25^\circ\text{C}$	I_R	25	60	uA
	$T_A=125^\circ\text{C}$		10	35	mA
Typical Thermal Resistance		$R_{\theta JA}$	90		°C/W

3A, 45V Low Forward Voltage Schottky Rectifier

RATINGS AND CHARACTERISTIC CURVES

$T_A=25^{\circ}\text{C}$ unless otherwise noted

FIG.1: Forward Output Current Derating Curve




FIG.2: Maximum Non-Repetitive Peak Forward Surge Current




FIG.3: Typical Forward Characteristics






FIG.4: Typical Reverse Characteristics



3A, 45V Low Forward Voltage Schottky Rectifier

PACKAGE OUTLINE DIMENSIONS



PACKING INFORMATION

Package	Reel(PCS)	Inner Box(PCS)	Carton(PCS)
SMA	5,000	10,000	80,000