


# 10A, 150V Low Forward Voltage Schottky Rectifiers

## FEATURES


- Trench MOS schottky barrier diode
- Low forward voltage drop
- Low power losses, high efficiency
- Moisture sensitivity: level 1, per J-STD-020
- High temperature soldering guaranteed: 260°C/10 seconds
- RoHS compliant

## TO-252



RoHS  
COMPLIANT

HALOGEN  
FREE  
AVAILABLE



## MECHANICAL DATA

- Case: TO-252
- Case material: molding compound meets UL 94V-0 flammability rating
- Polarity: as marked on case body

## TYPICAL APPLICATION

General purpose use in AC to DC bridge full wave rectification for SMPS, lighting, adapter, charger, home appliance, office equipment and telecommunication.

## MAXIMUM RATINGS

$T_A=25^\circ\text{C}$  unless otherwise noted

Parameter	Symbol	Value	Unit
Repetitive Peak Reverse Voltage	$V_{RRM}$	150	V
Average Forward Rectified Current	$I_{F(AV)}$	10	A
Peak Forward Surge Current (8.3 ms single half sine-wave superimposed on rated load)	$I_{FSM}$	80	A
Operating Junction Temperature Range	$T_J$	-55 to +150	$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55 to +150	$^\circ\text{C}$

## ELECTRICAL CHARACTERISTICS

$T_A=25^\circ\text{C}$  unless otherwise noted


Parameter	Test Conditions	Symbol	Value		Unit
			Typ.	Max.	
Forward Voltage@ $I_F=5\text{A}$	$T_A=25^\circ\text{C}$	$V_F$	0.82	0.85	V
	$T_A=125^\circ\text{C}$		0.74	0.77	V
Reverse Current @ $V_{RRM}$	$T_A=25^\circ\text{C}$	$I_R$	1	10	$\mu\text{A}$
	$T_A=125^\circ\text{C}$		0.6	5	mA
Typical Thermal Resistance		$R_{\theta JC}$	4		$^\circ\text{C}/\text{W}$

# 10A, 150V Low Forward Voltage Schottky Rectifiers


## RATINGS AND CHARACTERISTIC CURVES

$T_A=25^\circ\text{C}$  unless otherwise noted


**FIG.1: Forward Output Current Derating Curve**




**FIG.2: Maximum Non-Repetitive Peak Forward Surge Current**



**FIG.3: Typical Forward Characteristics**




**FIG.4: Typical Reverse Characteristics**



# 10A, 150V Low Forward Voltage Schottky Rectifiers

## PACKAGE OUTLINE DIMENSIONS



## PACKING INFORMATION

Package	Tube(PCS)	Inner Box(PCS)	Carton(PCS)
TO-252	80	4,000	20,000